

# MULTIPLEXERS & QUADS: Colour Quad Devices - VT2050Z

- "AUTO SYS", Auto switching between PAL and NTSC standards
- "AGC", Auto gain control
- Real time display picture
- High resolution picture
- "Zoom", VCR zoom playback function
- On screen "MENU" setup
- 8 character camera titles
- Time & Date generator and location setting
- Individual Dwell time setting
- Video loss detection & BUZZER setting
- Security lockout
- Alarm function, Alarm reset time setting, Alarm in NC./NO. setting
- Looping output
- Low power consumption
- Compact size



<b>MODEL NO.</b>	<b>VT2050Z</b>
<b>Camera Type</b>	Color ( NTSC or PAL )
<b>Video Input</b>	4 Camera + 1 VCR
<b>Dual system ( NTSC &amp; PAL )</b>	Yes
<b>Picture refresh rate fields / sec</b>	60 (50)
<b>Gain Control</b>	Auto
<b>Digital Memory</b>	1024 x 512
<b>VCR zoom</b>	Yes
<b>Video Output</b>	Monitor Out x 1, 1Vp-p, 75 ohms VCR OUT x 1, 1Vp-p, 75 ohms
<b>Looping out</b>	Yes
<b>Meun setup</b>	Yes
<b>Titles</b>	8 character titles for each camera
<b>Time &amp; Date</b>	Yes
<b>Video loss detection</b>	Yes
<b>Alarm Input</b>	NC. or NO. Sensor Input x 2
<b>Alarm Output</b>	NC. C. NO. Relay Contact Output, 24V DC / 1A
<b>Alarm duration</b>	1 to 99 Sec.
<b>Dwell time</b>	0 to 99 Sec.
<b>Buzzer</b>	Yes
<b>Security lock</b>	Yes
<b>Rack mountable</b>	Yes
<b>Power Source</b>	12V to 24V / AC or DC, 1A
<b>Power Consumption</b>	7 Watts
<b>Operation Temperature</b>	0° to 50°
<b>Dimension</b>	285mm(W) x 235mm(D) x 44mm(H)
<b>Weight</b>	2.5 Kgs (with power adaptor)

Available in Australia from



Available in New Zealand from

